



MASSEY FERGUSON

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: 23541

Issue date: 31/01/2023 Revision date: 27/03/2023 Supersedes version of: 12/03/2023 Version: 1.3

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : MF Super Engine Oil 15W-40  
Product code : 7402-99-203  
Type of product : Lubricant for diesel engines  
Product group : End product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
Use of the substance/mixture : Lubricants and additives  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Distributor

AGCO Ltd - Massey Ferguson Brand  
Abbey Park  
CV9 2TQ Stoneleigh Kenilworth  
United Kingdom  
T +44 (0) 2476 694 400  
[sds@uk.agcocorp.com](mailto:sds@uk.agcocorp.com)

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 2476 694 400

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates,hydrotreated heavy paraffinic	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 70 – < 90	Not classified
Zinc bis[O-(6-methylheptyl)]bis[O-(sec-butyl)]bis(dithiophosphate)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 REACH-no: 01-2119543726-33	≥ 1 – < 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
distillates (petroleum), hydrotreated heavy paraffinic; baseoil - unspecified substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25, UK-01-1759217276-5	≥ 0.1 – < 5	Asp. Tox. 1, H304
distillates (petroleum), solvent-dewaxed light paraffinic; baseoil - unspecified substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-48	≥ 0.1 – < 5	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, FI, GB, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 REACH-no: 01-2119471299-27, UK-01-0119695008-1	≥ 0.1 – < 5	Asp. Tox. 1, H304
paraffin oils (petroleum), catalytic dewaxed heavy	CAS-No.: 64742-70-7 EC-No.: 265-174-4 EC Index-No.: 649-477-00-2 REACH-no: 01-2119487080-42	≥ 0.1 – < 5	Asp. Tox. 1, H304

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Zinc bis[O-(6-methylheptyl)]bis[O-(sec-butyl)]bis(dithiophosphate)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 REACH-no: 01-2119543726-33	( 6.25 ≤C < 9.9) Skin Irrit. 2, H315 ( 10 ≤C < 12.5) Eye Irrit. 2, H319 ( 12.5 ≤C < 100) Eye Dam. 1, H318

Comments

: A petroleum product. DMSO extract < 3 % weight (IP 346)

Full text of H- and EUH-statements: see section 16

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Get medical advice/attention if you feel unwell. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None under normal use. Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: Although not classified, the product contains mineral oil. If aspirated into the lungs e.g. through vomiting after ingestion, admit to hospital immediately.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical, CO <sub>2</sub> , dry sand, or alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

#### 5.3. Advice for firefighters

Precautionary measures fire	: Keep container closed when not in use.
Firefighting instructions	: Prevent fire fighting water from entering the environment. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Self-contained breathing apparatus.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Evacuate unnecessary personnel. Caution : this product can cause the floor to be very slippery.

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if liquid enters sewers or public waters.

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clear up rapidly by scoop or vacuum. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Do not eat, drink or smoke when using this product.
- Hygiene measures : Wear personal protective equipment. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Store in a well-ventilated place. Keep container tightly closed.
- Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep container closed when not in use. Store in a dry place.
- Incompatible products : Oxidizing agent. Strong acids. Strong bases.
- Storage area : Store in a well-ventilated place.
- Special rules on packaging : Store in a closed container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Distillates,hydrotreated heavy paraffinic (64742-54-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).
distillates (petroleum), hydrotreated heavy paraffinic; baseoil - unspecified (64742-54-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).
distillates (petroleum), solvent-dewaxed light paraffinic; baseoil -unspecified (64742-56-9)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

#### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup> 8H
Regulatory reference	EU OEL (Europe).

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

###### Eye protection:

Chemical goggles or face shield

##### 8.2.2.2. Skin protection

No additional information available

##### 8.2.2.3. Respiratory protection

###### Respiratory protection:

No respiratory protection needed under normal use conditions

##### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber.
Appearance	: Liquid.
Odour	: mild.
Odour threshold	: Not available
Melting point	: -33 °C Pour Point
Freezing point	: Not available
Boiling point	: > 320 °C

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Flammability	: Not flammable, Heating may cause a fire.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 206 °C Pensky-Martens closed cup.
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 109 mm <sup>2</sup> /s @40°C
Solubility	: Material nearly insoluble in water. Soluble in organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: ≈ 7 Not determined. Typical for mineral oil
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≈ 0.873 @15.6°C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

Additional information : The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOCs may be present.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Extremely high or low temperatures. Moisture.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Distillates, hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>distillates (petroleum), hydrotreated heavy paraffinic; baseoil - unspecified (64742-54-7)</b>	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
<b>distillates (petroleum), solvent-dewaxed light paraffinic; baseoil -unspecified (64742-56-9)</b>	
LD50 oral rat	> 5000 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg Source: EHCA
LC50 Inhalation - Rat (Dust/Mist)	> 2.18 mg/l Source: ECHA
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
<b>Zinc bis[O-(6-methylheptyl)]bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)</b>	
LD50 oral rat	> 2600 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: Repeated exposure may cause skin dryness or cracking.
<b>Zinc bis[O-(6-methylheptyl)]bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)</b>	
Skin corrosion/irritation, Guinea pig	≥ 6.25 (4 Hours, (OECD 404 method))
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
<b>Zinc bis[O-(6-methylheptyl)]bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)</b>	
Serious eye damage/irritation, rabbit	10 ≥ 12.5 ≤ (504 Hours)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified
Additional information	: This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP346 test
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
<b>Zinc bis[O-(6-methylheptyl)]bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)</b>	
LOAEL (dermal, rat/rabbit, 90 days)	≈ 70 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (oral, rat, 90 days)	160 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Aspiration hazard	: Not classified
Additional information	: Although not classified, the product contains mineral oil. If aspirated into the lungs e.g. through vomiting after ingestion, admit to hospital immediately.
<b>MF Super Engine Oil 15W-40</b>	
Viscosity, kinematic	109 mm <sup>2</sup> /s @40°C
<b>Distillates,hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	40 mm <sup>2</sup> /s @40C

### 11.2. Information on other hazards

No additional information available

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 12: Ecological information

#### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

Additional information : Based on available data, the classification criteria are not met.

#### Distillates,hydrotreated heavy paraffinic (64742-54-7)

LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

#### distillates (petroleum), hydrotreated heavy paraffinic; baseoil - unspecified (64742-54-7)

LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

#### Zinc bis[O-(6-methylheptyl)]bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)

EC50 - Crustacea [1]	5.4 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	2.1 mg/l Test organisms (species): other:
EC50 72h - Algae [2]	2 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	2.1 mg/l Test organisms (species): other:
EC50 96h - Algae [2]	2 mg/l Test organisms (species): other:

#### 12.2. Persistence and degradability

##### MF Super Engine Oil 15W-40

Persistence and degradability : Not established.

#### 12.3. Bioaccumulative potential

##### MF Super Engine Oil 15W-40

Partition coefficient n-octanol/water (Log Kow) :  $\approx 7$  Not determined. Typical for mineral oil

#### Distillates,hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow) : 3.9 – 6 Source: IUCLID

#### distillates (petroleum), hydrotreated heavy paraffinic; baseoil - unspecified (64742-54-7)

Partition coefficient n-octanol/water (Log Pow) : 3.9 – 6 Source: IUCLID

#### distillates (petroleum), solvent-dewaxed light paraffinic; baseoil -unspecified (64742-56-9)

Partition coefficient n-octanol/water (Log Pow) : 3.9 – 6 Source: IUCLID

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Partition coefficient n-octanol/water (Log Pow) 3.9 – 6 Source: IUCLID

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to a hazardous or special waste collection point.  
European List of Waste (LoW) code : 13 02 05\* - mineral-based non-chlorinated engine, gear and lubricating oils  
HP Code : HP15 - "Waste capable of exhibiting a hazardous property listed above not directly displayed by the original waste".

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

#### 14.6. Special precautions for user

##### Overland transport

Not applicable

##### Transport by sea

Not applicable

##### Air transport

Not applicable

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Inland waterway transport

Not applicable

### Rail transport

Not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes version of	Modified	
13.1	European List of Waste (LoW) code	Added	

### Abbreviations and acronyms:

CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

# MF Super Engine Oil 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ATE	Acute Toxicity Estimate
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DNEL	Derived-No Effect Level
EC-No.	European Community number
ED	Endocrine disrupting properties
IARC	International Agency for Research on Cancer
LC50	Median lethal concentration
LD50	Median lethal dose
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
STP	Sewage treatment plant
VOC	Volatile Organic Compounds
WGK	Water Hazard Class
vPvB	Very Persistent and Very Bioaccumulative

Data sources : ECHA (European Chemicals Agency). REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. Supplier's safety documents.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.