

**Product Information Sheet:****Date:** 29/01/2015**Ref:** AP/SUT/03

AGCO Parts Super Universal Tractor Oil 10W-30

Massey Ferguson references:

VACC3547 5ltr

VACC3379 20ltr

VACC3378 205ltr

VACC3394 1000ltr

VACC3395 Bulk

Applications

Super Universal Tractor Oil 10W-30 is an agricultural lubricant specifically designed to solve, with only one product a range of lubrication requirements. Recommended for use in the following applications:

- Engine
- Transmissions
- Hydraulic systems
- Final drives
- Wet brakes and immersed clutches

Main Benefits

- Low temperature flow to facilitate starting, and giving rapid response in hydraulic systems;
- Enhanced filterability, and increased power for tools;

The excellent characteristics of this product are obtained by employing top quality additives.

Specifications

Can be used whenever the following specifications are required:

Engines (SAE 10W-30) :

API CG-4, MAN 271, MIL-L-2104D, MB 228.1, Ford M2C-121B

STOU Specifications :

MF M-1139, MF M-1144, Ford M2C 159B, John Deere JDM J27, ZF TE-ML 06C,07B

Transmissions :

API GL-4, MIL-L-2105, Allison C4, Cat TO-2 MF M1135, John Deere J20C, Ford M2C 134D, New Holland NH – 410B

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

Typical Characteristics

SAE Grade	10W-30
Density at 15 °C	0.881
Viscosity cSt at 100 °C	11.4
Viscosity cSt at 40 °C	74
Viscosity Index	140.0
Flash Point (closed) °C	190
Sulphated Ash	1.4
Pour Point °C	-37
TBN	10.5
FZG Gear Test, Pass load stage	11
Vickers Pump Wear (Wt. Loss mgs)	<50

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised