



Product Information:
MULTIVIS CST SS 10W-40
ENHANCED PROTECTION

Description

Multivis CST SS 10W-40 is a premium engine oil manufactured from advanced Group II base fluids and the latest additive technology. This grade is designed for use in petrol and diesel engines fitted to passenger cars and light commercial vehicles. Multivis CST SS 10W-40 will protect camshafts, critical valve gear and bearings from wear, even under severe cold start conditions, as well as controlling rust and corrosion.

Features

- Keeps components clean and the engine running efficiently
- Combats oxidation thickening, optimising fuel economy.
- Provides outstanding oil pressure, even at high temperatures

Applications

Multivis CST SS 10W-40 is recommended for use in 4-stroke petrol and diesel engines, including turbocharged and supercharged units, fitted in passenger cars and light commercial vehicles, where an oil of this type and specification is required.

Multivis CST SS 10W-40 can also be used in ATVs (with dry clutches), horticultural equipment and generators.

Performance Levels

API SP / CF

ACEA A3 / B4

MB 226.5

MB 229.3

PSA B71 2300

VW 501.01 / 505.00

Renault RN 0700 / 0710

Physical Characteristics

Viscosity @ 100 °C, cSt.	13.7
Viscosity @ 40 °C, cSt.	92.4
Viscosity Index	150
Density @ 15.6 °C	0.868
Flash Point (Closed) °C	203
TBN, mg/KOH/g	10
Pour Point, °C	-39

Figures based on average production values.

Part No.s: MUL001, MUL005, MUL025, MUL205

(TDS Multivis CST SS 10W-40 – 290824 Issue 5)

