

**Product Information Sheet:****Date:** 17/01/2011**Ref:** AP/HV46/02

---

## AGCO Parts HV Hydraulic Oil ISO 46

### AGCO Parts references:

---

VACC3467	5ltr
VACC3331	20ltr
VACC3330	205ltr
VACC3388	1000ltr
VACC3389	Bulk

### Applications

---

HV Hydraulic Oil ISO 46 is a mineral oil-based hydraulic fluid possessing a Viscosity Index (VI) greater than 130. It contains oxidation and corrosion-inhibitors, together with additives that minimize wear and foaming. The selection of shear stable VI-improvers ensures that the viscosity is maintained in service. This grade is intended for two main types of duty: such as in machinery subjected to very cold start-up conditions and high-temperature continuous running.

### Main Benefits

---

- Wide operating temperature range
- Easy cold start-up
- High degree of equipment protection
- Good filterability
- Excellent performance in anti-wear protection, oxidation resistance and thermal stability

### Specifications

---

DIN 51524 Part 3 (HVLP)  
Sperry Vickers I-286-S3, M-2950-S  
Denison HF-0 dry and wet T6C-020  
Denison HF-1, HF-2  
Poclair (HV 46)  
AFNOR E48-603 (HV:HM)  
ASLE 64.1 to 64.4, 70.1 to 70.3  
CETOP RP91H

## Storage

---

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

## Health, Safety and Environment

---

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

## Typical Characteristics

---

<b>ISO VG</b>	<b>HV46</b>
Density @ 15°C	0.881
Flash Point (closed) °C	195
Pour Point °C	-40
Viscosity cSt at 100 °	8.6
Viscosity cSt at 40 °C	47
Viscosity Index	>130
Vickers Pump Wear, wt loss mgs.	<50
FZG Gear Test, pass load	12
Rust Test (D-665)	Pass
Foaming Test	Pass

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply

with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised