



Product Information Sheet:

Date: 11/04/2016

Ref: AP/MPEO/03

AGCO Parts MP Engine Oil 15W-40

AGCO Parts references:

VACC3457 20ltr
VACC3458 205ltr

Applications

MP Engine Oil 15W-40 is a premium quality heavy duty multi-grade engine oil recommended for diesel powered vehicles, operating under varying work-loads. This grade is blended from high quality mineral oils and carefully selected additives to provide high levels of cleanliness, together with wear, rust and oxidation protection. This product also provides protection to petrol engines requiring an API SL performance level.

MP Engine Oil 15W-40 is suitable for use in agricultural and off-highway equipment, where an oil of this type and specification is called for.

Manufacturers include: Caterpillar, Cummins, DAF, ERF, Iveco, Leyland, MAN, Mercedes Benz, Perkins / Rolls Royce, Renault, Scania, Volvo, Caterpillar, JCB, John Deere, New Holland, Massey Ferguson, Komatsu, Hitachi, Case, Manitou, Ford, etc.

May also be used in transmissions, hydraulic systems, PTOs, compressors, etc. where a product of this type and specification is required.

Main Benefits

- Outstanding Soot Handling
- Enhanced Sludge Dispersancy
- High levels of Piston Cleanliness
- Improved Anti-wear protection

Specifications

ACEA E7
API CH-4/CF/SJ/SL
MB 228.3 / 229.1
MAN M3275
Volvo VDS2
RVI RLD 99
Cummins CES 20071 / 20072/ 20076 / 20077
MACK EO-M Plus
MTU TYPE 2
VW 505.00
Allison C4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

Typical Characteristics

SAE Classification	15W-40
Density at 15.6°C	0.885
Kinematic Viscosity at 100°C, cSt.	14.3
Kinematic Viscosity at 40°C, cSt.	99
Viscosity Index	140
Flash Point (Closed), °C	200
Pour Point, °C	-30
TBN, mg/KOH/g	11.0

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised