



Product Information Sheet:

Date: 20/01/2015

Ref: AP/PEO/02

AGCO Parts Premium Engine Oil 15W-40

AGCO Parts references:

VACC3377 20ltr
VACC3376 205ltr
VACC3396 1000ltr
VACC3397 Bulk

Applications

Premium Engine Oil 15W-40 is an advanced technology heavy-duty diesel engine oil, designed to meet the most severe lubrication requirements of North American and European heavy-duty diesel engines and complies with Volvo's VDS-3 performance category. This grade is suitable for use in Euro 2, Euro 3 and Euro 4 engines (including EGR versions).

Premium Engine Oil 15W-40 can be used in agricultural and off-highway equipment. where an oil of this type and specification is called for.

Recommended also heavy-duty diesel engines fitted in commercial vehicles such as Cummins, Daimler Chrysler, DAF, Mack, MAN, MTU, SCANIA and Volvo.

Main Benefits

- Outstanding Soot Handling
- Enhanced Sludge Dispersancy
- High levels of Piston Cleanliness
- Improved Anti-wear protection

Specifications

ACEA E7
API CI-4/SL
Caterpillar ECF-1
Cummins CES 20071 / 72, Cummins CES 20076 / 77 / 78
Global DHD-1
MB 228.3
MAN M3275
MACK EO-M Plus
MTU Type II quality
Volvo VDS3
Allison C4 quality

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

Typical Characteristics

SAE Classification	15W-40
Density	0.888
Kinematic Viscosity at 100 °C (cSt)	14.4
Kinematic Viscosity at 40 °C (cSt)	103
Viscosity Index	140
Closed Flash Point (°C)	192
Sulphated Ash (%)	1.2
Pour Point (°C)	-30
TBN mg/ KOH / g	10.0

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised