

**Product Information Sheet:****Date:** 20/01/2015**Ref:** AP/UTTO/02

AGCO Parts Transmission Plus 10W-30

AGCO Parts references:

| | |
|----------|---------|
| VACC3332 | 20ltr |
| VACC3333 | 205ltr |
| VACC3386 | 1000ltr |
| VACC3387 | Bulk |

Applications

Designed for use in tractor hydraulic / transmission systems, particularly those incorporating oil immersed brakes.

Transmission Plus 10W-30 is recommended for use in the following applications:

- Transmissions
- Hydraulic systems
- Final drives
- Wet brakes and immersed clutches
- Power Take-offs
- Power Steering

Key Benefits

Friction coefficient adapted for the latest transmission technology:

- Ensures excellent hydraulic response at low temperatures.
- Provides optimum friction control in oil immersed brakes and clutch systems.
- Protects transmission system components under conditions of shock load.
- Protects components subjected to arduous high temperature operation.

Specifications

Ford ESN-M2C134-A/B/C/D
Ford ESEN-M2C86-A/B
New Holland NH – 410B
Massey Ferguson M1135/1143
Volvo (WB101)
Volvo Transmission Oil 97303:020
John Deere J20A/C
Allison C4
Caterpillar TO-2
API GL4 (L20)
ZF TE-ML-03E/05F/06K

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

Typical Characteristics

| | |
|-----------------------------------|--------|
| SAE | 10W-30 |
| Density at 15 °C | 0.884 |
| Viscosity at 100 °C, cSt. | 9.6 |
| Viscosity at 40 °C, cSt. | 62 |
| Viscosity Index | 135 |
| Viscosity -18 °C (Brookfield), cP | 3500 |
| Flash Point (Closed), °C | 190 |
| Pour Point, °C | -45 |
| Foam Test | Pass |

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised