



SAFETY DATA SHEET

Liquimatic No. 1 (ISO 10)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Liquimatic No. 1 (ISO 10)
Product number 7595
Internal identification GHS21612

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hydraulic oil.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Morris Lubricants
Castle Foregate
Shrewsbury
Shropshire
SY1 2EL
+44 (0) 1743 232200
+44 (0) 1743 353584
sds@morris-lubricants.co.uk

Manufacturer MORRIS LUBRICANTS
Castle Foregate
Shrewsbury
Shropshire
SY1 2EL
UK
+44 (0) 1743 232200
+44 (0) 1743 353584
sds@morris-lubricants.co.uk

1.4. Emergency telephone number

Emergency telephone +44(0)1743 232200 (08.45 - 17.00 GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Asp. Tox. 1 - H304
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) -

2.2. Label elements

Liquimatic No. 1 (ISO 10)

Hazard pictograms



| | |
|---------------------------------|---|
| Signal word | Danger |
| Hazard statements | H304 May be fatal if swallowed and enters airways. |
| Precautionary statements | P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P405 Store locked up. P501a Dispose of contents/container to hazardous or special waste collection point. |
| Contains | Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based, Distillates,hydrotreated heavy paraffinic |

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|--|--|
| Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based | 60-100% |
| CAS number: 72623-86-0 | EC number: 276-737-9 |
| | REACH registration number: 01-2119474878-16-XXXX |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Asp. Tox. 1 - H304 | - |
| Distillates,hydrotreated heavy paraffinic | 10-30% |
| CAS number: 64742-54-7 | EC number: 265-157-1 |
| | REACH registration number: 01-2119484627-25-0014 |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Asp. Tox. 1 - H304 | - |
| Isopropyl oleate | <1% |
| CAS number: 112-11-8 | EC number: 203-935-4 |
| | REACH registration number: 01-2119976306-30-0000 |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Not Classified | - |
| Highly refined mineral oil (C15 - C50) | <1% |
| CAS number: — | |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Not Classified | - |

Liquimatic No. 1 (ISO 10)

| | |
|-----------------------|--|
| Mineral Oil | <1% |
| CAS number: — | |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Not Classified | - |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|---|
| General information | Get medical attention if any discomfort continues. |
| Inhalation | If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately. |
| Ingestion | Do not induce vomiting. Get medical attention immediately. |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. |
| Eye contact | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | If aspiration into the lungs is suspected, eg when vomiting, admit to hospital immediately. |
| Inhalation | Upper respiratory irritation. |
| Ingestion | The product contains mineral oil, which if aspirated into the lungs through vomiting after ingestion, may result in chemical pneumonia. May be fatal if swallowed and enters airways. |
| Skin contact | Prolonged contact may cause redness, irritation and dry skin. |
| Eye contact | Irritation of eyes and mucous membranes. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|------------------------|
| Notes for the doctor | Treat symptomatically. |
|-----------------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|---------------------------------------|--|
| Suitable extinguishing media | Extinguish with foam, carbon dioxide, dry powder or water fog. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |

5.2. Special hazards arising from the substance or mixture

| | |
|--------------------------------------|--|
| Specific hazards | Heat from fire could result in drums bursting |
| Hazardous combustion products | Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic. |

5.3. Advice for firefighters

| | |
|---|--|
| Protective actions during firefighting | Control run-off water by containing and keeping it out of sewers and watercourses. |
|---|--|

Liquimatic No. 1 (ISO 10)

Special protective equipment for firefighters Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Lubricating Oil (Petroleum) C15-30 hydrotreated neutral oil-based

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Distillates,hydrotreated heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5

Short-term exposure limit (15-minute): ACGIH 10 mg/m³

Isopropyl oleate

Long-term exposure limit (8-hour TWA): OES 5 mg/m³

Short-term exposure limit (15-minute): OES 10 mg/m³

Highly refined mineral oil (C15 - C50)

Liquimatic No. 1 (ISO 10)

Long-term exposure limit (8-hour TWA): 5 mg/m³

Mineral Oil

Long-term exposure limit (8-hour TWA): OES 5 mg/m³(c)

ACGIH = American Conference of Governmental Industrial Hygienists.

Octylamine (CAS: 111-86-4)

PNEC

Fresh water; 0.0002 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Use barrier creams to prevent skin contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Thermal hazards

Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.

Environmental exposure controls

Do not allow product to contaminate land.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---------------------------------|----------------------------------|
| Appearance | Liquid. |
| Colour | Straw. |
| Odour | Characteristic. Oil-like. |
| Odour threshold | Not determined. |
| pH | Not applicable. |
| Melting point | -44°C |
| Initial boiling point and range | >320°C @ 101.3 kPa |
| Flash point | 170°C Pensky-Martens closed cup. |

Liquimatic No. 1 (ISO 10)

| | |
|---|---|
| Upper/lower flammability or explosive limits | Not known. |
| Other flammability | Product is not flammable but on excessive heating may become combustible. |
| Vapour pressure | <0.1 kPa @ 20°C |
| Vapour density | Not determined. |
| Relative density | 0.840 @ 15.6°C |
| Solubility(ies) | Insoluble in water. Soluble in the following materials: Organic solvents. |
| Partition coefficient | Not determined. |
| Auto-ignition temperature | Not determined. |
| Decomposition Temperature | Not determined. |
| Viscosity | 10 cSt @ 40°C |
| Explosive properties | Not considered to be explosive. |
| Explosive under the influence of a flame | Not considered to be explosive. |
| Oxidising properties | The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising. |

9.2. Other information

| | |
|----------------------------------|---|
| Volatile organic compound | The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOCs may be present. |
|----------------------------------|---|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|---|
| Reactivity | There are no known reactivity hazards associated with this product. |
|-------------------|---|

10.2. Chemical stability

| | |
|------------------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. |
|------------------|---|

10.3. Possibility of hazardous reactions

| | |
|---|--|
| Possibility of hazardous reactions | Unlikely to occur under normal conditions of use. Unlikely to occur. |
|---|--|

10.4. Conditions to avoid

| | |
|----------------------------|---|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. |
|----------------------------|---|

10.5. Incompatible materials

| | |
|---------------------------|--------------------------|
| Materials to avoid | Strong oxidising agents. |
|---------------------------|--------------------------|

10.6. Hazardous decomposition products

| | |
|---|--|
| Hazardous decomposition products | Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . |
|---|--|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

| | |
|-------------------------------------|--|
| Notes (oral LD₅₀) | Not expected to be highly toxic based on information of ingredients. |
|-------------------------------------|--|

Liquimatic No. 1 (ISO 10)

Acute toxicity - dermal

Notes (dermal LD₅₀) Not expected to be highly toxic based on information of ingredients.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

Serious eye damage/irritation

Serious eye damage/irritation May cause mild, short lasting discomfort to eyes.

Respiratory sensitisation

Respiratory sensitisation Repeated exposure to oil mists may cause respiratory damage.

Skin sensitisation

Skin sensitisation Not expected to be a skin sensitizer based on information on components.

Reproductive toxicity

Reproductive toxicity - fertility No data available to suggest the product will cause reproductive toxicity.

Aspiration hazard

Aspiration hazard Kinematic viscosity <= 20.5 cSt @ 40 C. Poses an aspiration hazard.

Inhalation

May cause respiratory system irritation.

Ingestion

Aspiration into the lungs (e.g. through vomiting) after ingestion can be hazardous with possible resultant chemically induced pneumonia. May be fatal if swallowed and enters airways.

Skin contact

Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.

Eye contact

May cause temporary eye irritation.

Acute and chronic health hazards

Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: Ecological information

Ecotoxicity

The product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is not classed as being readily biodegradable by OECD test methods but is considered inherently biodegradable.

Stability (hydrolysis)

The product is based on highly refined mineral oils that are considered stable to hydrolysis.

Biodegradation

The product is not considered readily biodegradable, albeit the major constituents are expected to ultimately biodegrade.

Biological oxygen demand

Not determined.

Chemical oxygen demand

Not determined.

12.3. Bioaccumulative potential

Bioaccumulative potential

Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient

Not determined.

12.4. Mobility in soil

Liquimatic No. 1 (ISO 10)

Mobility The product is non-volatile. The product is insoluble in water and will spread on the water surface.

Henry's law constant Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class European Waste Catalogue (EWC) = 13 01 13* (other hydraulic oils)

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Liquimatic No. 1 (ISO 10)

| | |
|-----------------------------|--|
| National regulations | Health and Safety at Work etc. Act 1974 (as amended). The Pollution Prevention and Control Act 1999. Special Waste regulations 1996. Control of Pollution (Oil Storage) (England) Regulations 2001 The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). |
| EU legislation | Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |
| Guidance | Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations. |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines – PICCS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

SECTION 16: Other information

| | |
|----------------------------------|--|
| Revision comments | NOTE: Lines within the margin indicate significant changes from the previous revision. |
| Revision date | 07/02/2020 |
| Revision | 3 |
| Supersedes date | 20/04/2016 |
| SDS number | 21612 |
| Risk phrases in full | Not classified. |
| Hazard statements in full | H304 May be fatal if swallowed and enters airways. |

Liquimatic No. 1 (ISO 10)

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.