

Fendt Special Trans

Fendt References :

X903 708 001 000 10 ltr

Applications : A high performance gear oil designed for maximum reliability and trouble-free operation of the axle and power shift transmission, wet brakes. Used in final drives and hydraulic construction machinery, even in the toughest operating conditions.

This product is particularly suitable for use in heavy duty transmission components, such as construction powershift transmissions, side drives, final drives and wet brakes.

Specifically recommended for use in Fendt Katana machines.

It is also ideal use in hydraulic systems and has the following outstanding features:

Main Benefits :

- It provides excellent compatibility with transmission components and friction materials, where motor oils are no longer sufficient.
- It helps guarantee higher transmission powers and longer life of the clutches due to optimized friction control
- Excellent anti-wear additives ensures high durability at full operating performance

Specifications :

Fendt Special Trans meets the following specifications:

- Caterpillar TO-4
- GM Allison C-4 (SAE 10W and SAE 30)
- ZF TE-ML 03 C (for SAE 10W and SAE 30)

Health and Safety :

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified

Environmental information:

Used lubricants and empty containers should be disposed of through authorized specialist companies.

Date Created: 8th August 2014 Ref RZ/DH/01 Page 2 of 2