

## Fendt Power Grade 10W-40

### Fendt references:

---

FX991 500 455 5ltr  
FX991 500 451 20ltr  
FX991 500 452 205ltr  
FX991 500 453 Bulk  
FX991 500 454 IBC

Note – Not all sizes are available in all markets. Check local programmes for availability details.

### Description

---

A heavy duty diesel specific engine oil, manufactured from high performance base fluids coupled with powerful additive chemistry. The product will provide protection for units operating under severe operating conditions under a variety of loads.

### Applications

---

Fendt Power Grade 10W-40 has been developed for use in engines fitted with exhaust gas re-circulation (EGR) or SCR (Adblue) NOX reduction systems.

The product can be used in on-highway engines complying with Euro 4 and 5 emission standards and off-highway engines complying with Tier 3 / Stage 3, Interim Tier 4 / Stage 3B where a grade of this type is specified.

Equipment manufacturers include: Mercedes Benz, MTU, Deutz, Renault, DAF, Iveco, MAN, Scania, Volvo.

### Specifications

---

API CI-4  
ACEA E4 / E7  
MB 228.5  
Volvo VDS-3  
Scania LDF-2  
Global DHD-1  
MAN M3277  
MTU DDC Type 3  
Mack EO-M Plus  
Cummins CES 20077/78  
Renault Trucks RXD/RLD-2  
DAF Extended Drain  
Deutz DQCIII-05  
Deutz DQCIII-10

## Storage

---

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

## Health, Safety and Environment

---

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

## Typical Characteristics

---

Density @ 15.6 °C	0.857
Viscosity @ 100°C, cSt.	14.63
Viscosity @ 40°C, cSt.	100.80
Viscosity Index	150
Flash Point (Closed) °C	195
TBN, mg/KOH/g	9.70
Pour Point, °C	-30

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised