
Fendt Super Trans 85W-90 Gear Oil

Fendt references:

FX991 500 540 5ltr
FX991 500 521 20ltr
FX991 500 501 205ltr

Note – Not all sizes are available in all markets. Check local programmes for availability details.

Applications

Transmission fluid of international standard for very highly stressed hypoid axle drives and – unless otherwise required by manufacturers.

Also for use in difflocks and unsynchronized manual transmissions in cars, commercial vehicles (trucks, busses, farming and construction equipment) and motorcycles.

Main Benefits

Superior viscosity / temperature characteristics offering excellent cold flow properties and enhanced thermal stability.

- Excellent resistance to foaming and corrosion.
- Formulated from high quality base oils and employing sulphur / phosphorous EP additive technology
- Compatible with the conventional seal materials used with mineral oils.
- Provides effective wear protection even under severe load conditions ensuring longer component life

Specifications

API GL5
MIL-L-2105D
ZF TE-ML 05A/12E/16B/17B/19B/21A

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

Typical

Density at 15 °C	0.894
Viscosity at 100 °C, cSt	15.0
Viscosity at 40 °C, cSt.	140
Viscosity Index	107
Flash Point (Open) °C	220
Pour Point, °C	-30

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised