



MASSEY FERGUSON

Product Information Sheet:

Date: 23/09/2019

Ref: MF/PLF/03

MF Premium Engine LF Oil 15W-40 Engine Oil

Massey Ferguson references:

3933822M1 5 ltr
3933823M1 20 ltr
3933824M1 205ltr

Note – Not all sizes are available in all markets. Check local programmes for availability details.

Applications

MF Premium Engine LF Oil 15W-40 is an advanced technology heavy duty diesel engine oil, incorporating the latest additive chemistry to meet and exceed current Massey Ferguson engine requirements.

It is designed for use in Massey Ferguson equipment that is operating under demanding conditions under a variety of workloads. This product can be used in Interim Tier 4 / stage 3B units without diesel particulate filters (DPFs).

Main Benefits

- It provides excellent protection against engine wear and deposit accumulation.
- Outstanding sludge dispersancy
- High levels of cleanliness, and soot handling contributing to longer engine life and reduced maintenance costs.

Specifications

ACEA E7
API CI-4/SL
Caterpillar ECF-1, ECF-2
Cummins CES 20071 / 72
Cummins CES 20076 / 77 / 78
Global DHD-1
MB 228.3
MAN M3275
MACK EO-M Plus
RVI RLD2
MTU Type 2
Volvo VDS3

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

Typical Characteristics

SAE Classification	15W-40
Density @ 15.6°C	0.888
Viscosity @ 100 °C, cSt	14.4
Viscosity @ 40 °C, cSt	103
Viscosity Index	140
Flash Point (closed) °C	92
Sulphated Ash (%Wt.)	1.2
Pour Point (°C)	-30
TBN, mg/KOH/g	10.0

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised