



MASSEY FERGUSON

Product Information Sheet:

Date: 04/02/2015

Ref: MF/PEO/04

MF Premium Engine Oil 10W-40 Engine Oil

Massey Ferguson references:

3933304M1 5 ltr
3933050M2 20 ltr
3933048M1 205ltr
3933047M2 Bulk
3933305M1 1000 ltr IBC

Note – Not all sizes are available in all markets.
Check local programmes for availability details.

Applications

MF Premium Engine Oil 10W-40 is a high performance fuel-efficient, long drain, engine oil for use in the latest clean fuels engines fitted on Massey Ferguson equipment.

It is designed for use in MF equipment that are operating under demanding conditions in all climates. Formulated using high quality non-conventional base oils, in combination with high quality performance additives,

Main Benefits

- It provides excellent protection against engine wear and deposit accumulation.
- High levels of cleanliness, and soot handling contributing to longer engine life and reduced maintenance costs.
- Fuel-efficient compared to conventional 15W-40 engine oils contributing to reduced operating costs.
- Lower fuel consumption and exhaust emissions means less harm to the environment.
- The SAE 10W-40 viscosity grade provides good low temperature oil flow properties to enable rapid lubrication after cold starting.

Specifications

API CI-4
ACEA E4 / E7
MB 228.5
Volvo VDS-3
Scania LDF-2
Global DHD-1
MAN M3277
MTU DDC Type 3
Mack EO-M Plus
Cummins CES 20077/78
Renault Trucks RXD/RLD-2
Deutz DQCIII-05 / Deutz DQCIII-10

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

Typical Characteristics

SAE Classification	10W-40
Density at 15 °C	0.88
Kinematic Viscosity at 100 °C, cSt.	14.5
Kinematic Viscosity at 40 °C, cSt.	95
Viscosity Index	154
Flash Point (Closed) °C	210
Sulphated Ash, %Wt.	1.45
Pour Point, °C	-35
TBN, mg/KOH/g	12.6

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised