



MASSEY FERGUSON

Product Information Sheet:

Date: 03/08/2020

Ref: MF/SEO/06

MF Super Engine Oil 15W-40

Massey Ferguson references:

3931040M4 5 ltr
3933054M2 20 ltr
3933052M2 205 ltr
3933387M1 IBC (1000 ltrs)

Note – Not all sizes are available in all markets. Check local programmes for availability details.

Applications

MF Super Engine Oil 15W-40 is designed for use in Massey Ferguson equipment operating under demanding conditions.

It is formulated using high quality conventional base oils in combination with high performance additives to provide good protection against wear and deposit accumulation.

MF Super Engine Oil 15W-40 is designed for longer drain intervals in accordance with the Massey Ferguson owner manual.

Main Benefits

- MF Super Engine Oil 15W-40 provides the following benefits:
- Long drain intervals in accordance with the engine manufacturer recommendations
- High levels of engine cleanliness and wear protection in turbo and non-turbo charged diesel engines.
- The SAE 15W-40 viscosity grade provides good low temperature oil flow properties.

Specifications

MF Super Engine Oil 15W-40 meets the following specifications:

ACEA E7, API CH-4 / SJ, MB 228.3, MAN M3275, Volvo VDS2
RVI RLD 99, Cummins CES 20071 / 20072/ 20076 / 20077, MACK EO-M Plus

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

Typical Characteristics

SAE Classification	15W-40
Density	0.873
Kinematic Viscosity at 100 °C (cSt)	14.8
Kinematic Viscosity at 40 °C (cSt)	108
Viscosity Index	140
Closed Flash Point (°C)	200
Sulphated Ash (%)	1.4
Pour Point (°C)	-33
TBN mg/ KOH / g	11.0

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised