

VALMAX ULTRA PLUS 15W-40

High Super High Performance Eco-Power Diesel Engine Oil Description

VALMAX ULTRA PLUS 15W-40 incorporates advanced technology additive systems to meet ACEA E7 and exceed the severe lubrication requirements of Europe, Japan and North American engine builders.

This product is specifically designed for low emission Euro 3 and Euro 4 engines, running under arduous conditions of extended oil drain and high workload.

VALMAX ULTRA PLUS 15W-40 is designed for agricultural diesel engines but is also recommended for wide application diesel fleet operators including bus, coach, haulage and plant demanding a technically advanced grade. It offers outstanding soot handling, enhanced sludge dispersancy and high levels of piston cleanliness, combined with low emissions and improved anti-wear protection.

Performance Levels

Valmax Ultra Plus 15W-40 meets or exceeds the following specifications and performance levels:

ACEA E7
API CH-4 / CF / SJ / SL
MB 228.3
Caterpillar ECF-1a, ECF-2
MAN M3275
Volvo VDS3
RVI RLD-2
Cummins CES 20076 / 20077 /20078
MACK EO-N
MTU TYPE 2
Global DHD-1

Physical Characteristics

Density	0.870
Kinematic Viscosity at 100 °C (cSt)	14.94
Kinematic Viscosity at 40 °C (cSt)	107.12
Viscosity Index	140
Closed Flash Point (°C)	209
Pour Point (°C)	-33
TBN mg/ KOH / g	11.2

Part numbers:

VACC3001	205ltr
VACC3002	25ltr
VACC3003	5ltr