



Product Information:
GROUNDFORCE SAE 30
Horticultural Engine Oil

Description

Groundforce SAE 30 is a low ash lubricant designed for use in older horticultural equipment powered by petrol and diesel engines where monograde oils are recommended. The oil is blended from solvent refined base stocks and performance additives to control vanish, soot, dispersancy, low temperature sludge, oxidation, rust and corrosion.

Groundforce SAE 30 is particularly suitable where machinery has to be laid up between seasons or for plant that is only used intermittently. It prevents internal deterioration caused by damp atmospheres and the extremes of temperatures.

Applications

For use in older diesel and petrol engines in horticultural equipment where an oil to API SF/CC quality is required.

Performance Levels

API SF/CC

Groundforce SAE 30 is approved and endorsed by the British Agricultural & Garden Machinery Association.

Physical Characteristics

| | |
|-------------------------------------|--------------|
| Appearance | Amber liquid |
| Density at 15.6 °C | 0.875 |
| Kinematic Viscosity at 100 °C (cSt) | 11.4 |
| Kinematic Viscosity at 40 °C (cSt) | 89.9 |
| Viscosity Index | 115 |
| Closed Flash Point (°C) | 210 |
| Pour Point (°C) | -36 |
| TBN (mgKOH/g) | 8.0 |

Figures based on average production values.

Part No.s: SAE001, SAE005, SAE025, SAE205

(TDS Groundforce 30 – 250116 Issue 3)

